

PS2 cabinet keyboard GER, 19" with Touchpad, for devices with suitable connector additional information, amount and content: see technical data

### General information

Product type designation	PS/2 membrane keyboard (GER), touchpad
--------------------------	--

### Control elements

#### Keyboard fonts

- |   |  |
|---|--|
| <ul style="list-style-type: none"> <li>• Design</li> <li>• Keyboard assignment</li> <li>• Function keys                             <ul style="list-style-type: none"> <li>— Number of function keys</li> <li>— Programmable</li> </ul> </li> <li>• Number pad</li> </ul> | Membrane keyboard<br>B3F, 101/102 or 104/105 OMRON<br>12<br>Yes<br>Yes |
|---|--|

#### Connection type

- |  |     |
|--|-----|
| <ul style="list-style-type: none"> <li>• PS/2</li> </ul> | Yes |
|--|-----|

#### Frame size/design

- |  |                                  |
|--|----------------------------------|
| <ul style="list-style-type: none"> <li>• Standard</li> </ul> | Yes; For industrial applications |
|--|----------------------------------|

### Input current

Current consumption (rated value)	25 mA; Typical
-----------------------------------	----------------

### Battery

Battery charge indicator	No; maintenance-free
--------------------------	----------------------

### Degree and class of protection

IP (at the front)	IP65
Splashproof	Yes

### Standards, approvals, certificates

CE mark	Yes
RoHS conformity	Yes

### Ambient conditions

#### Ambient temperature during operation

- |  |               |
|--|---------------|
| <ul style="list-style-type: none"> <li>• min.</li> <li>• max.</li> </ul> | 0 °C<br>40 °C |
|--|---------------|

#### Ambient temperature during storage/transportation

- |  |                 |
|--|-----------------|
| <ul style="list-style-type: none"> <li>• min.</li> <li>• max.</li> </ul> | -10 °C<br>50 °C |
|--|-----------------|

Relative humidity	
-------------------	--

- Operation, max. 90 %; no condensation
- Condensation permissible No

### Mechanics/material

- Material
  - Sheet steel Yes
- Enclosure material (front)
  - Plastic Yes; AUTOTEX (R) V150

### Service life

- Number of operating cycles, keys 1 000 000; Operations (minimum)

### Dimensions

- Width 482.6 mm
- Height 42.5 mm
- Depth 177.8 mm

### Weights

- Weight without packaging 1 480 g
- Weight incl. packaging 1 665 g

### Scope of supply

- Delivery quantity in pieces 1; Built-in keyboard rack mounting

### Other

- Target devices Suitable for IPC and HMI devices with the corresponding interfaces (see manual)

### Usable in the following products

- Product 1 [6AV2124-0GC13-0AX0](#)
- Product 2 [6AV2124-0QC13-0AX0](#)

**last modified:** 07/06/2017