

SIMATIC DP, 5 ELECTRON. MODULES FOR ET 200S, 4 DO HIGH FEATURE DC 24V/0.5A, 15 MM WIDTH DIAGNOSIS SHORT CIRCUIT, SF-LED 5 PIECES PER PACKAGING UNIT



Figure similar

Supply voltage	
Reverse voltage protection	Yes; when using the same load voltage as on the power module
Load voltage L+	
<ul style="list-style-type: none"> <li>Rated value (DC)</li> </ul>	24 V; From power module
<ul style="list-style-type: none"> <li>Reverse polarity protection</li> </ul>	Yes; polarity reversal can lead to the digital outputs being connected through
Input current	
from load voltage L+ (without load), max.	5 mA; Per channel
from backplane bus 3.3 V DC, max.	10 mA
Power loss	
Power loss, typ.	0.8 W
Address area	
Address space per module	
<ul style="list-style-type: none"> <li>with packing</li> </ul>	4 bit
<ul style="list-style-type: none"> <li>without packing</li> </ul>	1 byte
Digital outputs	

Number of digital outputs	4
Short-circuit protection	Yes
• Response threshold, typ.	0.7 to 1.5 A
Limitation of inductive shutdown voltage to	-55 to -60 V, L+( )
Controlling a digital input	Yes
<b>Switching capacity of the outputs</b>	
• on lamp load, max.	5 W
<b>Load resistance range</b>	
• lower limit	48 Ω
• upper limit	3 400 Ω
<b>Output voltage</b>	
• for signal "1", min.	L+ (-1 V)
<b>Output current</b>	
• for signal "1" rated value	0.5 A
• for signal "1" permissible range, min.	7 mA
• for signal "1" permissible range, max.	600 mA
• for signal "0" residual current, max.	0.3 mA
<b>Output delay with resistive load</b>	
• "0" to "1", max.	100 μs
• "1" to "0", max.	300 μs
<b>Parallel switching of two outputs</b>	
• for uprating	No
• for redundant control of a load	Yes; per module
<b>Switching frequency</b>	
• with resistive load, max.	100 Hz
• with inductive load, max.	2 Hz
• on lamp load, max.	10 Hz
<b>Total current of the outputs</b>	
• Current per module, max.	2 A
<b>Cable length</b>	
• shielded, max.	1 000 m
• unshielded, max.	600 m
<b>Isochronous mode</b>	
Isochronous operation (application synchronized up to terminal)	Yes
<b>Interrupts/diagnostics/status information</b>	
Diagnostic functions	Yes
<b>Diagnostic messages</b>	
• Short-circuit	Yes; Module-wise
<b>Diagnostics indication LED</b>	
• Group error SF (red)	Yes

- Status indicator digital output (green) Yes; Per channel

### Parameter

Remark 3 byte

### Potential separation

#### Potential separation digital outputs

- between the channels No
- between the channels and backplane bus Yes

### Isolation

Isolation tested with 500 V DC

### Dimensions

Width 15 mm

Height 81 mm

Depth 52 mm

### Weights

Weight, approx. 40 g

**last modified:** 03/07/2017