

### Product type designation

### C-PLUG

C-PLUG, replaceable medium for simple device exchange in case of failure, for storage of configuration or user data and application data applicable in SIMATIC NET products with C-Plug slot



### Permitted ambient conditions

Ambient temperature	
<ul style="list-style-type: none"> <li>during operation</li> </ul>	-40 ... +75 °C
<ul style="list-style-type: none"> <li>during storage</li> </ul>	-40 ... +80 °C
<ul style="list-style-type: none"> <li>during transport</li> </ul>	-40 ... +80 °C
Relative humidity	
<ul style="list-style-type: none"> <li>at 25 °C / without condensation / during operation / maximum</li> </ul>	95 %
Protection class IP	IP20

### Design, dimensions and weight

Width	24.3 mm
Height	17 mm
Depth	8.1 mm
Net weight	5 g
design of the removable storage	
<ul style="list-style-type: none"> <li>C-PLUG</li> </ul>	Yes
<ul style="list-style-type: none"> <li>KEY-PLUG</li> </ul>	No
Product feature / conformal coating	No

## Product properties, functions, components / general

Storage capacity 32 Mibyte

## Further Information / Internet Links

### Internet-Link

- to website: TIA Selection Tool <http://www.siemens.com/tia-selection-tool>
- to website: Selector SIMATIC NET SELECTION TOOL <http://www.siemens.com/snst>
- to the website: IWLAN <http://www.siemens.com/iwlan>
- to website: Industrial communication <http://www.siemens.com/simatic-net>
- to website: Industry Mall <https://mall.industry.siemens.com>
- to website: Information and Download Center <http://www.siemens.com/industry/infocenter>
- to website: Image database <http://automation.siemens.com/bilddb>
- to website: CAx Download Manager <http://www.siemens.com/cax>
- to website: Industry Online Support <https://support.industry.siemens.com>

**last modified:**

06/09/2017