



MLFB-Ordering data: **1LE1001-1AC42-2GB4**

Motor type: **1AV2104C**

Client order no.:

Item no.:

Order no.:

Consignment no.:

Offer no.:

Project:

Remarks:

U [V]	Δ/Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	NOM. EFF at ... load [%]			Power factor at ... load			I <sub>A</sub> /I <sub>N</sub> I/I <sub>N</sub>	M <sub>A</sub> /M <sub>N</sub> T <sub>f</sub> /T <sub>N</sub>	M <sub>k</sub> /M <sub>N</sub> T <sub>B</sub> /T <sub>N</sub>	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4				
230	Δ	50	1.50	- / -	6.50	970	15.0	79.8	80.5	79.0	0.73	0.65	0.52	5.4	2.0	2.8	IE2
400	Y	50	1.50	- / -	3.70	970	15.0	79.8	80.5	79.0	0.73	0.65	0.52	5.4	2.0	2.8	IE2
460	Y	60	1.75	- / -	3.45	1170	14.0	86.5	87.1	85.8	0.74	0.67	0.55	5.8	1.9	2.8	IE2
460	Y	60	1.50	- / -	3.15	1175	12.0	86.5	86.3	84.2	0.69	0.61	0.49	6.4	2.2	3.2	IE2
IM V1 / IM 3011		FS 100 L		25 kg	IP55	CC032A	IEC/EN 60034		IEC, DIN, ISO, VDE, EN								

Mechanical data			Terminal box	
Sound pressure level 50Hz/60Hz (load)	59 dB(A)	62 dB(A)	Terminal box position	top
Moment of inertia	0.011 kg m <sup>2</sup>		Material of terminal box	Aluminium
Bearing DE   NDE	6206 2Z C3	6206 2Z C3	Type of terminal box	TB1 F00
Bearing lifetime	40000 h		Contact screw thread	M4
Lubricants	Esso Unirex N3		Max. cross-sectional area	4.0 mm <sup>2</sup>
Regreasing device	No		Cable diameter from ... to ...	11.0 mm - 21.0 mm
Grease nipple	- / -		Cable entry	2xM32x1,5-1xM16x1,5
Type of bearing	Preloaded bearing DE		Cable gland	3 plugs
Condensate drainage holes	No		Special design	
External earthing terminal	No			
Vibration class	A			
Insulation	155(F) to 130(B)			
Duty type	S1			
Direction of rotation	bidirectional			
Frame material	aluminum			
Data of anti condensation heating	- / -			
Coating	Standard paint finish C2			
Color	RAL7030			
Motor protection	(B) 3 PTC thermistors - for tripping (2 terminals)			
Method of cooling	IC411 - self ventilated, surface cooled			

Environmental conditions	
Ambient temperature	-20 °C - +40 °C
Altitude above sea level	1000 m