

Product type designation

IE/PB-Link PN IO

IE/PB LINK PN IO Gateway BETWEEN IND. WITH PROFINET IO FUNCTIONALITY, WITH PROFINET IO FUNCTIONALITY, S7-ROUTING AND DATA BLOCK ROUTING, 10/100 MBIT FAST ETHERNET, 9.6 KBIT/S TO 12 MBITS PROFIBUS



Transmission rate

Transfer rate

- | | |
|---|--------------------------|
| • at the 1st interface | 10 ... 100 Mbit/s |
| • at the 1st interface / acc. to PROFIBUS | 9.6 kbit/s ... 12 Mbit/s |

Interfaces

| | |
|--|----------------------------|
| Number of interfaces / acc. to Industrial Ethernet | 1 |
| Number of electrical connections | |
| • at the 1st interface / acc. to Industrial Ethernet | 1 |
| • at the 1st interface / acc. to PROFIBUS | 1 |
| • for power supply | 1 |
| Type of electrical connection | |
| • at the 1st interface / acc. to PROFIBUS | 9-pin Sub-D socket (RS485) |
| • at the 1st interface / acc. to Industrial Ethernet | RJ45 port |
| • for power supply | 2-pole terminal block |
| design of the removable storage / C-PLUG | Yes |

Supply voltage, current consumption, power loss

| | |
|---|----|
| Type of voltage / of the supply voltage | DC |
|---|----|

| | |
|--|-------|
| Supply voltage / external | 24 V |
| Supply voltage / external / at DC / Rated value | 24 V |
| Relative positive tolerance / at DC / at 24 V | 5 % |
| Relative negative tolerance / at DC / at 24 V | 5 % |
| Consumed current | |
| <ul style="list-style-type: none"> • from external supply voltage / at DC / at 24 V / maximum | 0.6 A |
| Power loss [W] | 10 W |

Permitted ambient conditions

| | |
|--|----------------|
| Ambient temperature | |
| <ul style="list-style-type: none"> • during operation | 0 ... 60 °C |
| <ul style="list-style-type: none"> • during storage | -40 ... +70 °C |
| <ul style="list-style-type: none"> • during transport | -40 ... +70 °C |
| Relative humidity / at 25 °C / without condensation / during operation / maximum | 95 % |
| Protection class IP | IP20 |

Design, dimensions and weight

| | |
|---------------|------------------------------------|
| Module format | Compact module S7-300 double width |
| Width | 80 mm |
| Height | 125 mm |
| Depth | 120 mm |
| Net weight | 0.6 kg |

Performance data / PROFIBUS DP

| | |
|---|-----------|
| Service / as DP master | |
| <ul style="list-style-type: none"> • DPV1 | Yes |
| Number of DP slaves / on DP master / usable | 64 |
| Amount of data | |
| <ul style="list-style-type: none"> • of the address area of the inputs / as DP master / total | 2048 byte |
| <ul style="list-style-type: none"> • of the address area of the outputs / as DP master / total | 2048 byte |
| <ul style="list-style-type: none"> • of the address area of the inputs / per DP slave | 244 byte |
| <ul style="list-style-type: none"> • of the address area of the outputs / per DP slave | 244 byte |

Performance data / S7 communication

| | |
|---|----|
| Number of possible connections / for S7 communication | |
| <ul style="list-style-type: none"> • maximum | 32 |

Performance data / multi-protocol mode

| | |
|---|----|
| Number of active connections / with multi-protocol mode | 48 |
|---|----|

Performance data / PROFINET communication / as PN IO-Device

Product function / PROFINET IO device Yes

Performance data / telecontrol

Protocol / is supported

- TCP/IP Yes

Product function / MIB support Yes

Protocol / is supported

- SNMP v1 Yes

Configuration software

- required STEP 7 V5.4 or higher or STEP 7 Professional (TIA Portal) V11 or higher

Product functions / Routing

Service / as PROFIBUS / dataset routing Yes

Number of possible connections / at data record routing / maximum 32

Product functions / Time

Product function / pass on time synchronization Yes

Further Information / Internet Links

Internet-Link

- to website: Selector SIMATIC NET SELECTION TOOL <http://www.siemens.com/snst>
- to website: Industrial communication <http://www.siemens.com/simatic-net>
- to website: Industry Mall <https://mall.industry.siemens.com>
- to website: Information and Download Center <http://www.siemens.com/industry/infocenter>
- to website: Image database <http://automation.siemens.com/bilddb>
- to website: CAx Download Manager <http://www.siemens.com/cax>
- to website: Industry Online Support <https://support.industry.siemens.com>

Security information

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

06/08/2017