

Product type designation

RF620R ETSI reader

SIMATIC RF600 READER RF620R ETSI; INTERFACE RS422 FOR TIA- INTEGRATION WITH INTEGRATED ANTENNA IP65, -25 UO TO +55 DEG C (WITHOUT ACCESSORIES)



Suitability for operation	RF600 transponder, for connecting to communication modules
Wireless frequencies	
Operating frequency	865 ... 868 MHz
Effective radiant power	
• minimum	65 mW
• maximum	800 mW
Electrical data	
Range / maximum	5 m
Protocol / with radio transmission	EPCglobal Class 1 Gen 2 / ISO 18000-6C
Transfer rate / with radio transmission / maximum	320 kbit/s
Product feature / multitag-capable	Yes
Polarization	circular
Transfer rate / at the point-to-point connection / serial / maximum	115.2 kbit/s
Transmission time / for user data	
• for write access / per byte / typical	6.3 ms
• for read access / per byte / typical	1 ms

Interfaces	
Standard for interfaces / for communication	RS422
Type of electrical connection	M12, 8-pin
<ul style="list-style-type: none"> • for communications interface 	M12, 8-pin
Mechanical data	
Material	Aluminum, ABS (GF20)
Color	silver/pastel turquoise
Mounting distance / relating to metal surfaces / recommended / minimum	0 mm
Supply voltage, current consumption, power loss	
Supply voltage	
<ul style="list-style-type: none"> • at DC / Rated value 	24 V
<ul style="list-style-type: none"> • at DC 	21.6 ... 30 V
Consumed current / at DC / at 24 V	
<ul style="list-style-type: none"> • typical 	0.395 A
<ul style="list-style-type: none"> • maximum 	0.47 A
Permitted ambient conditions	
Ambient temperature	
<ul style="list-style-type: none"> • during operation 	-25 ... +55 °C
<ul style="list-style-type: none"> • during storage 	-40 ... +85 °C
<ul style="list-style-type: none"> • during transport 	-40 ... +85 °C
Ambient condition / for operation	With operating temperature below -20 °C: Warming-up time at least 10 minutes
Protection class IP	IP65
Shock resistance	EN 60068-2-27, EN 60068-2-6
Shock acceleration	500 m/s ²
Vibrational acceleration	200 m/s ²
Design, dimensions and weight	
Width	193 mm
Height	252 mm
Depth	52 mm
Net weight	1.85 kg
Mounting type	4 x M6 screws, Vesa 100 with 4 x M4 screws
Wire length	
<ul style="list-style-type: none"> • for RS 422 interface / maximum 	100 m
Product properties, functions, components / general	
Display version	3-color LED
Product feature / silicon-free	Yes
Standards, specifications, approvals	
Certificate of suitability	Wireless according to R&TTE guideline, CE, IEC 60950

MTBF

18 y

Accessories

Further Information / Internet Links

Internet-Link

- to website: Selector SIMATIC NET SELECTION TOOL
- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

<https://support.industry.siemens.com/cs/ww/en/view/67384964>

<http://www.siemens.com/ident/rfid>

<https://mall.industry.siemens.com>

<http://www.siemens.com/industry/infocenter>

<http://automation.siemens.com/bilddb>

<http://www.siemens.com/cax>

<https://support.industry.siemens.com>

last modified:

08/10/2017