SIEMENS

Data sheet

6ES7972-0BA60-0XA0

Product type designation

Product description



PROFIBUS bus connector, RS485, Fast Connect, without PG socket, 35°

PROFIBUS bus connector, RS485, Fast Connect, without PG socket, 35°

SPARE PART SIMATIC DP,BUS CONNECTOR FOR PROFIBUS UP TO 12 MBIT/S 35 DEGREE ANGLE CABLE OUTLET, IPCD TECHOLOGY FAST CONNECT, WITHOUT PG SOCKET 15,8 X 54 X 39,5 MM (WXHXD),

Suitability for use	For connecting PROFIBUS nodes to the PROFIBUS bus cable
Transmission rate	
Transfer rate / with PROFIBUS DP	9.6 kbit/s 12 Mbit/s
Interfaces	
Number of electrical connections	
• for PROFIBUS cables	2
• for network components or terminal equipment	1
Type of electrical connection	
• for PROFIBUS cables	Integrated insulation displacement contacts for 2-core PB FC-installation cables
• for network components or terminal equipment	Sub-D connector (9-pin)
Type of electrical connection / FastConnect	Yes
Mechanical data	
Design of terminating resistor	Integrated resistor combination that can be selected with slide switch

Material / of the enclosure	plastic	
Locking mechanism design	Screw	
Design, dimensions and weight		
Type of cable outlet	35° cable outlet	
Width	15.8 mm	
Height	54 mm	
Depth	39.5 mm	
Net weight	29 g	
Permitted ambient conditions		
Ambient temperature		
during operation	-25 +60 °C	
during storage	-40 +70 °C	
during transport	-40 +70 °C	
Protection class IP	IP20	
Product properties, functions, components / general		
Product feature		
• silicon-free	Yes	
Product component		
 PG connection socket 	No	
• strain relief	Yes	
Standards, specifications, approvals		
Certificate of suitability		
 RoHS conformity 	Yes	
UL approval	Yes	
last modified:	03/14/2017	