

\*\*\* SPARE PART\*\*\* SIMATIC S7-200, TD200C CUSTOMIZABLE TEXT DISPLAY FOR S7-200, 2 LINES, WITH CABLE (2.5M) AND MOUNTING ACCESSORIES, CONFIGURATION WITH STEP7-MICRO/WIN



Figure similar

| Display  |   |
|--|---|
| Design of display  | LCD backlit   |
| Line display   |   |
| <ul style="list-style-type: none"> <li>Number of lines</li> <li>Number of characters per line</li> <li>Character size</li> </ul> | 2<br>20; Characters/line: ASCII, cyrillic; 10 characters/line: Chinese<br>5 mm  |
| Supply voltage   |   |
| Rated value (DC)   | 24 V; Power supply via the S7-200 communications interface or optional external power supply unit; the CPU sensor power supply (24 V DC) is not subjected to load |
| Input current  |   |
| Current consumption, max.  | 120 mA  |
| Interfaces   |   |
| Point-to-point   |   |
| <ul style="list-style-type: none"> <li>Transmission rate, max.</li> </ul>  | 187.5 kbit/s  |
| 1. Interface   |   |

|  |                                   |
|--|-----------------------------------|
| Physics  | RS 485                            |
| <b>Functionality</b>                                     |                                   |
| • PPI  | Yes                               |
| — Number of nodes, max.                                  | 126; S7-200, OP, TP, TBP, PG / PC |
| <b>Degree and class of protection</b>                    |                                   |
| IP (at the front)  | IP65                              |
| <b>Ambient conditions</b>                                |                                   |
| <b>Ambient temperature during operation</b>              |                                   |
| • min.   | 0 °C                              |
| • max.   | 60 °C                             |
| <b>Ambient temperature during storage/transportation</b> |                                   |
| • min.   | -20 °C                            |
| • max.   | 70 °C                             |
| <b>Dimensions</b>  |                                   |
| Width  | 148 mm                            |
| Height   | 76 mm                             |
| Depth  | 28 mm                             |
| Mounting cutout, width                                   | 138 mm                            |
| Mounting cutout, height                                  | 68 mm                             |
| Cabinet/switchboard thickness                            | 0.3 mm; 0.3 to 4 mm               |
| <b>Weights</b>   |                                   |
| Weight, approx.  | 200 g                             |
| <b>last modified:</b>                                    | 03/11/2017                        |