

SIPLUS S7-300 ISOLATION MODULE - 25...+ 60 DGR C WITH CONFORMAL COATING BASED ON 6ES7195-7KF00-0XA0 . SEPARATOR MODULE BETWEEN F- AND STANDARD MODULES WITH REDUNDANT ET200M INTERFACE MODULES USE ONLY WITH SEPARATOR BUS MODULE



Standards, approvals, certificates	
CE mark	Yes
UL approval	Yes; File E239877
FM approval	Yes; CofC 3028431
Ambient conditions	
Ambient temperature during operation	
• min.	-25 °C; = Tmin
• max.	60 °C; = Tmax
Ambient temperature during storage/transportation	
• min.	-40 °C
• max.	70 °C
Extended ambient conditions	
• relative to ambient temperature-atmospheric pressure-installation altitude	Tmin ... Tmax at 1080 hPa ... 795 hPa (-1000 m ... +2000 m)
Relative humidity	
— With condensation, tested in accordance with IEC 60068-2-38, max.	100 %; RH incl. condensation/frost (no commissioning under condensation conditions)
Resistance	

- against biologically active substances /  
conformity with EN 60721-3-3
- against chemically active substances /  
conformity with EN 60721-3-3
- against mechanically active substances /  
conformity with EN 60721-3-3

Yes

Yes

Yes

#### Accessories

belongs to product

ET 200M

#### Weights

Weight, approx.

10 g

**last modified:**

05/25/2017