

SPARE PART SIPLUS HCS716I POWER OUTPUT MODULE LA716 WITH 16 CHANNELS EACH MAX. 650W. FOR USE A MODULES SUBRACK IS REQUIRED. THE 5 X 20 MM FUSES 5 AMP. QUICK-RESPONSE FOR EACH CHANNEL ARE PLUGGED ON OPEN FUSE HOLDERS AND ARE EXCHANGEABLE. 2-PHASE POWER SUPPLY VIA FRONT SIDE 3-POLE TERMINALS. HEATER OUTLETS VIA 2 X 8-PIN CONNECTORS (NOT IN THE SCOPE OF SUPPLY).



Figure similar

General information	
Product brand name	SIPLUS
Product designation	HCS716I power module LA716
Type of control of heat emitters	Full-wave control
Installation type/mounting	
Mounting type	Mounting clip in the rack
Mounting position	vertical
Type of ventilation	Self ventilation or forced ventilation
Supply voltage	
Type of supply voltage	AC
Rated value (AC)	230 V
Relative negative tolerance	18 %
Relative positive tolerance	15 %
Resistance thermometer (RTD)	
<ul style="list-style-type: none"> Design of electrical connection for supply voltage 	Terminal, 3-pin

— Connectable conductor cross-sections, solid	1x (0.5 ... 6 mm ²)
— Connectable conductor cross-sections, finely stranded with wire end processing	1x (0.5 ... 4 mm ²)
— Connectable conductor cross-sections for AWG cables	22 ... 10

Power electronics

Type of load	Ohmic load
Heating power	
• Power carrying capacity per output, max.	650 W
Integration and conversion time/resolution per channel	
• Design of electrical connection at output for heating and fan	Socket strip, 8-pole
— Connectable conductor cross-sections, solid	1x (0.2 ... 1.5 mm ²)

Interfaces

Interfaces/bus type	system interface
---------------------	------------------

Interrupts/diagnostics/status information

Diagnostics function	Voltage diagnostics
Diagnostic messages	
• Wire-break	Yes
• Fuse blown	Yes
• Heat emitter defect	Yes

Integrated Functions

Monitoring functions	
• Temperature monitoring	Yes

Potential separation

Design of electrical isolation between the outputs	Optocoupler between main circuit and SELV / PELV
	No

EMC

EMC interference emission	in accordance with EN 61000-6-4:2007 + A1:2011
Electrostatic discharge acc. to IEC 61000-4-2	4 kV contact discharge / 8 kV air discharge
Field-related interference acc. to IEC 61000-4-3	10 V/m (80 ... 1 000 MHz), 3 V/m (1.4 ... 2.0 GHz), 1 V/m (2.0 ... 2.7 GHz)
Conducted interference due to burst acc. to IEC 61000-4-4	2 kV voltage supply cables / 2 kV signal cables
Conducted interference due to surge acc. to IEC 61000-4-5	on power supply and signal cables: 1 kV symmetrical, 2 kV unsymmetrical
Conducted interference due to high-frequency radiation acc. to IEC 61000-4-6	10 V (0.15 ... 80 MHz)

Degree and class of protection

IP degree of protection	IP00
-------------------------	------

Standards, approvals, certificates

Certificate of suitability	CE, KCC
KC approval	Yes
EAC (formerly Gost-R)	Yes
China RoHS compliance	Yes

Ambient conditions

Ambient temperature during operation

- min. 0 °C
- max. 55 °C

Ambient temperature during storage/transportation

- Storage, min. -40 °C
- Storage, max. 70 °C
- Transportation, min. -40 °C
- Transportation, max. 70 °C

Air pressure acc. to IEC 60068-2-13

- Operation, min. 860 hPa
- Operation, max. 1 080 hPa
- Storage, min. 660 hPa
- Storage, max. 1 080 hPa
- Installation altitude above sea level, max. 2 000 m

Shock testing

- Shock resistance acc. to IEC 60068-2-27 15 g / 11 ms / 3 shocks/axis
- Shock resistance acc. to IEC 60068-2-29 25 g / 6 ms / 1 000 shocks/axis

Dimensions

Width	31 mm
Height	233.4 mm
Depth	241 mm

last modified: 06/03/2017