

*** SPARE PART*** SIMATIC S7-MODULAR EMBEDDED CONTROLLER, EC31, 1 GB RAM, 2 GB FLASH DISK WITH PREINSTALLED SW: WINDOWS XP EMBEDDED; INTERFACES: 1. IF: 2X PROFINET, 2. IF: 1X FAST ETHERNET, 3. IF: 2 X USB, MMC SLOT, DOCUMENTATION ON CD/DVD, RESTORE CD/DVD



Figure similar

General information	
Product type designation	SIMATIC S7-mEC, EC31
Hardware product version	04
Firmware version	V1.3
PC configuration	
Computer platform	SIMATIC S7 modular embedded controller
Processor	Intel Core Duo 1.2 GHz
Main memory	1 GB RAM
Flash Disk	2 GB
Operating systems	Windows XP embedded SP2 FP2007
Supply voltage	
Rated value (DC)	
• 24 V DC	Yes
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Mains buffering	
• Mains/voltage failure stored energy time	5 ms

Input current	
Rated value at 24 V DC	800 mA; without backplane bus and USB power supply
Power loss	
Power loss, typ.	34 W
Memory	
Type of memory	256 KB non-volatile memory for retentive data
Work memory	
• integrated	1 Gbyte
Hardware configuration	
Integrated power supply	Yes
Interfaces	
USB port	2 x USB 2.0 high speed/high current
serial interface	0
Industrial Ethernet	
• Industrial Ethernet interface	X1: 2 ports 10/100 Mbit/s (ERTEC-based) X2: 1 port 10/100 Mbit/s
EMC	
Emission of radio interference acc. to EN 55 011	
• Limit class A, for use in industrial areas	Yes
Degree and class of protection	
Degree of protection acc. to EN 60529	
• IP20	Yes
Standards, approvals, certificates	
CE mark	Yes
CSA approval	Yes; Included in cULus
cULus	Yes
FM approval	Yes
RCM (formerly C-TICK)	Yes
Ambient conditions	
Ambient temperature during operation	
• min.	0 °C
• max.	50 °C
Ambient temperature during storage/transportation	
• min.	-40 °C
• max.	70 °C
Vibrations	
• Operation, tested according to IEC 60068-2-6	Yes
• Transport, tested acc. to IEC 60068-2-6	Yes
Shock test	

- tested according to IEC 60068-2-27
- tested according to IEC 60068-2-29

Yes

Yes

Dimensions

Width	160 mm
Height	125 mm
Depth	115 mm
last modified:	03/24/2017