

SIMATIC DP, HART ANALOG INPUT SM 331, 8 AI, 0/4 - 20MA
HART, FOR ET200M WITH IM153-2, 20 PIN



Figure similar

Supply voltage

Load voltage L+

- Rated value (DC) 24 V
- Reverse polarity protection Yes

Input current

from load voltage L+ (without load), max.	20 mA
from backplane bus 5 V DC, max.	120 mA

Output voltage

Power supply to the transmitters

- Rated value (DC) 24 V

Power loss

Power loss, typ.	1.5 W
------------------	-------

Analog inputs

Number of analog inputs	8
• For resistance measurement	0

permissible input current for current input (destruction limit), max.	40 mA
Input ranges	
• Current	Yes
Input ranges (rated values), currents	
• 0 to 20 mA	Yes
• Input resistance (0 to 20 mA)	125 Ω
• -20 mA to +20 mA	Yes
• Input resistance (-20 mA to +20 mA)	125 Ω
• 4 mA to 20 mA	Yes
• Input resistance (4 mA to 20 mA)	125 Ω
Cable length	
• shielded, max.	800 m
Analog value generation for the inputs	
Measurement principle	Sigma Delta
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	16 bit
• Integration time, parameterizable	Yes
• Integration time (ms)	20 ms at 50 Hz; 16.6 ms at 60 Hz; 100 ms at 100 Hz
• Interference voltage suppression for interference frequency f1 in Hz	10 / 50 / 60 Hz
Encoder	
Connection of signal encoders	
• for current measurement as 2-wire transducer	Yes
• for current measurement as 4-wire transducer	Yes
Errors/accuracies	
Operational error limit in overall temperature range	
• Current, relative to input range, (+/-)	0.15 %
Basic error limit (operational limit at 25 °C)	
• Current, relative to input range, (+/-)	0.1 %
Interrupts/diagnostics/status information	
Diagnostic functions	Yes
Alarms	
• Diagnostic alarm	Yes
• Limit value alarm	Yes
Diagnostic messages	
• Diagnostic information readable	Yes
Diagnostics indication LED	
• Group error SF (red)	Yes
Potential separation	

Potential separation analog inputs

- between the channels and backplane bus

Yes

Isolation

Isolation tested with 500

Connection method

required front connector 20-pin

Dimensions

Width 40 mm

Height 125 mm

Depth 117 mm

Weights

Weight, approx. 205 g

last modified: 03/24/2017