

### Product type designation

### CP 342-5

COMMUNICATIONSPROCESSOR CP342-5 FOR CONNECTING SIMATIC S7-300 TO PROFIBUS, DP, S5-COMPATIBLE PG/OP AND S7 COMMUNICATION



### Transmission rate

#### Transfer rate

- at the 1st interface / acc. to PROFIBUS

9.6 kbit/s ... 12 Mbit/s

### Interfaces

Number of interfaces / acc. to Industrial Ethernet

0

Number of electrical connections

- at the 1st interface / acc. to PROFIBUS
- for power supply

1

1

Type of electrical connection

- at the 1st interface / acc. to PROFIBUS
- for power supply

9-pin Sub-D socket (RS485)

4-pole terminal block

### Supply voltage, current consumption, power loss

Type of voltage / of the supply voltage

DC

Supply voltage / 1 / from backplane bus

5 V

Supply voltage

24 V

Supply voltage / external

24 V

Supply voltage / external / at DC / Rated value

24 V

Relative positive tolerance / at DC / at 24 V	20 %
Relative negative tolerance / at DC / at 24 V	15 %
Consumed current	
• from backplane bus / at DC / at 5 V / typical	0.15 A
• from external supply voltage / at DC / at 24 V / typical	0.25 A
Power loss [W]	5 W

#### Permitted ambient conditions

Ambient temperature	
• during operation	0 ... 60 °C
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
Relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
Protection class IP	IP20

#### Design, dimensions and weight

Module format	Compact module S7-300 single width
Width	40 mm
Height	125 mm
Depth	120 mm
Net weight	0.3 kg
Mounting type	
• S7-300 rail mounting	Yes

#### Product properties, functions, components / general

Number of units	
• per CPU / maximum	4

#### Performance data / open communication

Number of possible connections / for open communication / by means of SEND/RECEIVE blocks / maximum	16
Amount of data	
• as user data per connection / for open communication / by means of SEND/RECEIVE blocks / maximum	240 byte

#### Performance data / PROFIBUS DP

Service / as DP master	
• DPV0	Yes
Number of DP slaves / on DP master / usable	124
Amount of data	
• of the address area of the inputs / as DP master / total	2160 byte

<ul style="list-style-type: none"> <li>• of the address area of the outputs / as DP master / total</li> </ul>	2160 byte
<ul style="list-style-type: none"> <li>• of the address area of the inputs / per DP slave</li> </ul>	244 byte
<ul style="list-style-type: none"> <li>• of the address area of the outputs / per DP slave</li> </ul>	244 byte
<ul style="list-style-type: none"> <li>• of the address area of the diagnostic data / per DP slave</li> </ul>	240 byte
Service / as DP slave	
<ul style="list-style-type: none"> <li>• DPV0</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• DPV1</li> </ul>	No
Amount of data	
<ul style="list-style-type: none"> <li>• of the address area of the inputs / as DP slave / total</li> </ul>	240 byte
<ul style="list-style-type: none"> <li>• of the address area of the outputs / as DP slave / total</li> </ul>	240 byte

#### Performance data / S7 communication

Number of possible connections / for S7 communication	
<ul style="list-style-type: none"> <li>• maximum</li> </ul>	16

#### Performance data / multi-protocol mode

Number of active connections / with multi-protocol mode	
<ul style="list-style-type: none"> <li>• without DP / maximum</li> </ul>	32
<ul style="list-style-type: none"> <li>• with DP / maximum</li> </ul>	28

#### Performance data / telecontrol

Protocol / is supported	
<ul style="list-style-type: none"> <li>• TCP/IP</li> </ul>	No
Configuration software	
<ul style="list-style-type: none"> <li>• required</li> </ul>	STEP 7 V5.1 SP2 or higher

#### Further Information / Internet Links

Internet-Link	
<ul style="list-style-type: none"> <li>• to website: Selector SIMATIC NET SELECTION TOOL</li> </ul>	<a href="http://www.siemens.com/snst">http://www.siemens.com/snst</a>
<ul style="list-style-type: none"> <li>• to website: Industrial communication</li> </ul>	<a href="http://www.siemens.com/simatic-net">http://www.siemens.com/simatic-net</a>
<ul style="list-style-type: none"> <li>• to website: Industry Mall</li> </ul>	<a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a>
<ul style="list-style-type: none"> <li>• to website: Information and Download Center</li> </ul>	<a href="http://www.siemens.com/industry/infocenter">http://www.siemens.com/industry/infocenter</a>
<ul style="list-style-type: none"> <li>• to website: Image database</li> </ul>	<a href="http://automation.siemens.com/bilddb">http://automation.siemens.com/bilddb</a>
<ul style="list-style-type: none"> <li>• to website: CAx Download Manager</li> </ul>	<a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a>
<ul style="list-style-type: none"> <li>• to website: Industry Online Support</li> </ul>	<a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>

#### Security information

---

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

**last modified:**

06/15/2017