

SIMATIC S7-300, DIGITAL INPUT SM 321, GALVANICALLY ISOLATED, 16 DI, DC 24V, 1 X 20 PIN, PROCESS INTERRUPT, DIAGNOSTICS, FIT FOR ISOCHRONONE MODE



Figure similar

Supply voltage	
Load voltage L+	
• Rated value (DC)	24 V
• permissible range, lower limit (DC)	20.4 V
• permissible range, upper limit (DC)	28.8 V
Input current	
from load voltage L+ (without load), max.	90 mA
from backplane bus 5 V DC, max.	130 mA
Power loss	
Power loss, typ.	4 W
Digital inputs	
Number of digital inputs	16
Input characteristic curve in accordance with IEC 61131, type 2	Yes
Number of simultaneously controllable inputs	
horizontal installation	

— up to 40 °C, max.	16
— up to 60 °C, max.	16
<b>vertical installation</b>	
— up to 40 °C, max.	16
<b>Input voltage</b>	
• Type of input voltage	DC
• Rated value (DC)	24 V
• for signal "0"	-30 to +5V
• for signal "1"	13 to 30V
<b>Input current</b>	
• for signal "1", typ.	7 mA
<b>Input delay (for rated value of input voltage)</b>	
for standard inputs	
— parameterizable	Yes; 0.1 / 0.5 / 3 / 15 / 20 ms
<b>Cable length</b>	
• shielded, max.	1 000 m
• unshielded, max.	600 m
<b>Encoder</b>	
<b>Connectable encoders</b>	
• 2-wire sensor	Yes
— permissible quiescent current (2-wire sensor), max.	2 mA
<b>Isochronous mode</b>	
Isochronous operation (application synchronized up to terminal)	Yes
<b>Interrupts/diagnostics/status information</b>	
Diagnostic functions	Yes; Parameterizable
<b>Alarms</b>	
• Diagnostic alarm	Yes; Parameterizable
• Hardware interrupt	Yes; Parameterizable
<b>Diagnostic messages</b>	
• Wire-break	Yes; to I < 1 mA
<b>Diagnostics indication LED</b>	
• Group error SF (red)	Yes
• Status indicator digital input (green)	Yes
<b>Potential separation</b>	
<b>Potential separation digital inputs</b>	
• between the channels	No
• between the channels, in groups of	16
• between the channels and backplane bus	Yes; Optocoupler

## Isolation

Isolation tested with	500 V DC
-----------------------	----------

## Connection method

required front connector	20-pin
--------------------------	--------

## Dimensions

Width	40 mm
-------	-------

Height	125 mm
--------	--------

Depth	120 mm
-------	--------

## Weights

Weight, approx.	200 g
-----------------	-------

<b>last modified:</b>	03/23/2017
-----------------------	------------