

Product type designation

**Bus terminal RS 485 (3m)**

RS 485 BUS TERMINAL FOR PROFIBUS TRANSMISSION RATE  
9.6 KBIT/S TO 1500 KBIT/S WITH CONNECTING CABLE 3.0 M



### Electrical data

Transfer rate / with PROFIBUS	9.6 kbit/s ... 1.5 Mbit/s
-------------------------------	---------------------------

### Interfaces

Number of electrical connections	2
<ul style="list-style-type: none"> <li>• for PROFIBUS cables</li> </ul>	
Type of electrical connection	Screw terminals
<ul style="list-style-type: none"> <li>• for PROFIBUS cables</li> </ul>	

### Mechanical data

Material / of the enclosure	plastic
-----------------------------	---------

### Design, dimensions and weight

Width	50 mm
Height	138 mm
Depth	53 mm
Net weight	360 g
Mounting type	Yes
<ul style="list-style-type: none"> <li>• 35 mm DIN rail mounting</li> </ul>	

## Further Information / Internet Links

### Internet-Link

- to website: Selector SIMATIC NET SELECTION TOOL <http://www.siemens.com/snst>
- to website: Industrial communication <http://www.siemens.com/simatic-net>
- to website: Industry Mall <https://mall.industry.siemens.com>
- to website: Information and Download Center <http://www.siemens.com/industry/infocenter>
- to website: Image database <http://automation.siemens.com/bilddb>
- to website: CAx Download Manager <http://www.siemens.com/cax>
- to website: Industry Online Support <https://support.industry.siemens.com>

**last modified:**

06/05/2017