

MICROMASTER 4 COMMUTATING CHOKE 380-600 V 3AC 45,8A  
 FOOTPRINT FSD - 0.41 MH NOT FOOTPRINT FOR V20



Figure similar

Order number	
Phase number / of the input voltage	3
Type of voltage / of the input voltage	AC
Input voltage	380 ... 600
Output current / rated value	45.8 A
Power loss [W]	
• at 50 Hz	Wert fehlt!
• at 60 Hz	Wert fehlt!
Type of electrical connection	
• for mains supply line	screw-type terminal
• for load-side outgoing feeder	Pigtail
Type of connectable conductor cross-section / for load-side outgoing feeder	Wert fehlt!
Connectable conductor cross-section	
• for mains supply line	Wert fehlt!
• for load-side outgoing feeder	16 mm <sup>2</sup>
Wire length / of connecting cable / for load-side outgoing feeder	0.79 m

Type of electrical connection / for PE conductor	M8 stud
Protection class IP	IP20
Width	275 mm
Height	520 mm
Depth	83.5 mm
Net weight	13 kg
Certificate of suitability	cURus

#### Further information

##### **Information und Download Center**

[https://www.automation.siemens.com/mcms/infocenter/content/en/Pages/order\\_form.aspx](https://www.automation.siemens.com/mcms/infocenter/content/en/Pages/order_form.aspx)

##### **Technical documentation**

<http://w3.siemens.com/mcms/mc-solutions/en/motion-control/support/technical-documentation/Pages/technical-documentation.aspx>

##### **Industry Mall**

<https://eb.automation.siemens.com/mall/en/WW/Catag/Product/6SE6400-3CC04-4DD0/all>

##### **Industry Online Support**

<http://support.automation.siemens.com/WW/view/en/6SE6400-3CC04-4DD0/all>